| <b>≘ GADMU</b>                 | What's New     Company     Produ  | ıcts   _ Support   _ Or | nline Store   Site Map                   |    |  |
|--------------------------------|---|-------------------------|--|----|--|
| <b>GARMII</b>                  |   | Search:                 |  | Go |  |
| Mobile                         | <u>Home</u> > <u>Products</u> > <u>Outdoor</u> > Rino 110   | Search.                 |  | 30 |  |
| Electronics                    | GPS III Plus  |                         |  |    |  |
| GPS III Plus                   | Specifications  | <b>K</b>                |  |    |  |
| Specifications Screen Examples | Plotter/Moving Map Features   | h                       |  |    |  |
| Testimonials                   | Dollar detailed Asserting Highway   | Adam Call Balanca       |  |    |  |
| Accessories                    | Basemap: Built-in detailed <u>Americas Highway</u> or <u>namericas Highway</u> or <u>namericas Highway</u> or <u>namericas Highway</u> , secondary roads in metro areas, cities, in the namericas Highways, secondary roads in metro areas, cities, in the namericas Highway or <u>namericas Highway</u> or <u></u> | national/state          | Download PDF Specs                       |    |  |
| Manuals Updates & Downloads    | detailed exit database for the Federal Highway sys  | stem in the US only     | *Requires Adobe Reader 5.0+ Get Acrobat- |    |  |
| FAQs                           | MapSource®: Compatible with most Garmin® Maccepts up to 1.44 megabytes of downloaded map  |                         | Adobe Reader                             |    |  |
| PC                             | Map Scale: Screen-width scale (500 feet to 3,000  | ,                       |  |    |  |
| F                              | Navigation Features   |                         |  |    |  |
| - "                            | Waypoints:  |                         |  |    |  |
|                                | <ul> <li>Total: 500 each with name, symbol, comment, and map display option</li> <li>Nearest: 9 (automatic) continuously updated</li> </ul>   |                         |  |    |  |
|                                | Routes: 20 reversible routes with up to 30 waypoints each, plus MOB and TracBack® modes   |                         |  |    |  |
|                                | Track Log: 1900 points  |                         |  |    |  |
|                                | Map Datums: 106   |                         |  |    |  |
|                                | Coordinates: Lat/Lon, UTM/UPS, MGRS, Loran TDs, plus other grids, including Maidenhead and User Grid  |                         |  |    |  |
|                                | Performance   | h                       |  |    |  |
|                                | Receiver: Differential-ready 12 parallel channel receiver continuously tracks and uses up to twelve satellites to compute and update a position   |                         |  |    |  |
|                                | Acquisition Times:  |                         |  |    |  |
|                                | <ul><li>Warm: approx. 15 seconds</li><li>Cold: approx. 45 seconds</li></ul>   |                         |  |    |  |
|                                | <ul> <li>Autolocate <sup>™</sup>: approx. 5 minutes</li> <li>EZinit <sup>™</sup>: easy initialization, 45 seconds</li> </ul>  |                         |  |    |  |
|                                | Update Rate: 1 second, continuous   |                         |  |    |  |
|                                | Accuracy:   |                         |  |    |  |
|                                | • Position:   |                         |  |    |  |
|                                | <ul> <li>15 meters (49 feet) RMS*</li> <li>1-5 meters (3-15 feet) RMS with Garmin GBR 21 DGPS receiver (optional)</li> <li>Velocity: 0.1 knot RMS steady state</li> </ul>   |                         |  |    |  |
|                                | Dynamics: 6g's  |                         |  |    |  |
|                                | Interfaces: NMEA 0183 and RTCM 104 DGPS corrections   |                         |  |    |  |
|                                | Antenna: Detachable with standard BNC connector   |                         |  |    |  |
|                                | Physical  | h                       |  |    |  |
|                                | Size: 2.32 H x 5 L x 1.62 W inches (5.9 x 12.7 x 4.1 cm)  |                         |  |    |  |
|                                | Weight: 9 ounces (255g) w/ batteries  |                         |  |    |  |
|                                | Display: 2.2 W x 1.5 H inches (5.6 x 3.8 cm) high-contrast electroluminescent backlit FTN display; switchable   |                         |  |    |  |

1 of 2

Garmin: GPS III Plus Specifications

orientation (100 x 160 pixels with gray scale)

Memory: Internal lithium battery lasts up to 10 years

Power

Source: 10-32 VDC (4 AA batteries)

Usage: 0.75 watts

Battery Life: Up to 36 hours

Specifications are subject to change without notice.

\* Subject to accuracy degradation to 100m 2DRMS under the United States Department of Defense-imposed Selective Availability Program.

h





Copyright 1996-2005 Garmin Ltd. or its subsidiaries Privacy Statement/Terms of Use

2 of 2